SECURE MICR PRINTERS

ST9917

- Small Footprint
- Performance & Security
- Entry-level Pricing



Model No.	ST9917	
Print Speed (pages/min.)	Up to 38 ppm	
Time to First Page	As fast as 6 seconds	
Maximum Duty Cycle (pgs./mo.)	Up to 120,000	
Recommended Volume (pgs./mo.)	2,000 - 15,000	
Maximum Resolution	Black: 1200 x 1200 dpi 1200 IQ (1200 x 600 dpi)	
Processor	Dual Core 1.0 GHz	
Memory (Standard/Max)	512MB / 512MB	
Standard Connectivity	Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A) USB 2.0 Specification Hi-Speed Certified (Type B) 802.11b/g/n/ac + Apple iBeacon	
Duplex Printing	2-sided: Integrated Duplex	
Paper Input Capacity Standard (in/out) Maximum (in/out)	Standard: 350 pages 20 lb or 75 gsm bond Maximum: 900 pages 20 lb or 75 gsm bond	
Paper Output Capacity	150 pages 20 lb or 75 gsm bond	
Printer Languages	PCL 5, PCLm, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, PDF-1.7 emulation, Direct Image	
Operator's Panel	2.8-inch (7.2 cm) Color Touch Screen	
MICR Cartridge Yields*	Starter: 1.5k, Replacement: 5k	
Imaging Unit**	Up to: 45K pages, based on 3 average letter/A4-size pages per print job at a 5% coverage	
Dimensions (in. H x W x D)	10.4 x 15.7 x 15.3 in	
Weight (lbs.)	29.8 lbs	
Warranty	1-year, return-to-depot from date of sale	
Quality Assurance Features	MICR Guarantee to ANSI / ABA Standards Auto Density Control MICR Toner Detection Low Toner Warning and Auto Stop Optimized Fusing & Transfer Voltage Originally Manufactured MICR Toner Regulated Fuser Temperature	
Secure Fonts	E-13B MICR Font CMC7 MICR Font Microprint Font Secure Numeric Font ICR Numeric Font	
Security Features	Set Copies to one (1) Password Protection Trusted Platform Module Auto Jam Recovery Disable Physical Drawer Lock "Optional" (TPM)	
Options	250 Sheet Tray Drawer Locks 550 Sheet Tray	
Wireless	Yes	
Wireless Network	WEP Encryption (64- and 128-bit key), 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, WPA2™ - Personal	

^{*} Average standard page yield value declared in accordance with ISO/IEC 19752.

^{**} Actual yield may vary. All specifications are subject to change without notice.



Secure MICR Printer- ST9917

MICR Feature	Description	Benefit
E13B Font	Widely accepted MICR font used in printing MICR encoded documents in the US, Canada, Mexico, the Far-East and some other countries.	Meets ASC X9B/US specification for MICR font and necessary to process checks through the system.
CMC7 Font	Alternative MICR font used to print MICR encoded documents in many European and most Latin American countries. Numeric character set only.	Meets international standards (ISO) 1004.
Secure Numeric Font	Unique ST-designed font that is very difficult to alter because of a special background and very small text & numeric print embedded in the amount line of the check.	Additional layer of security at the document level. Minimizes the risk of fraud.
Microprint Font	Extremely small type font allows one to embed micro text and numbers inside lines of print on the MICR document. Denoted by the letters "MP."	Additional layer of security at the document level. Minimizes the risk of fraud.
ICR Numeric Font	Image readable secure font designed to be read by imaging equipment utilized by many financial institutions.	Additional layer of security at the document level. Minimizes the risk of fraud.
Set Copies to one (1)	A PCL setting that tells the printer to print the job only once.	Prevents fraud by disallowing the printing of multiple copies of a document.
Auto Jam Recovery Disable	Automatically turns Jam Recovery OFF when checks are being printed.	Prevents multiple copies of a check from being printed.
Password Protection	Prevents access to check-printing resources (stored signatures, MICR fonts, form overlays) without the proper password.	Prevents unauthorized access to MICR and Secure fonts, and user-specific signatures and form overlays.
MICR Toner	Device only uses MICR toner.	Prevents printing of MICR documents with regular toner- preventing costly bank rejects.
Toner Low Warnings	Printer alerts user when MICR toner is low.	Ensures quality MICR printing.
3 Year MICR Guarantee to ANSI/ABA Standards	Source Technologies ensures the readability. performance of our MICR printers.	Ensures the quality of printed negotiable documents.
Auto Density Control for Toner	Ensures conformance to signal strength standards throughout cartridge life.	Ensures conformance and bank acceptance.
Originally Manufactured MICR Toner Cartridge	Toner cartridges are built and tested using MICR toner.	No "refilled" or "remanufactured" cartridges to introduce potential problems that would damage the printer.
Regulated Fuser Temperature for Optimum Performance	Fusing temperature controlled to match MICR toner and check stock paper weights.	Maximizes toner adherence. Less exposure to fraud due to less toner lift off.



Supported Operating Systems

Microsoft Windows Operating Systems Supported	Windows Server 2008 x64 running Terminal Services, Windows 11, Windows Server 2008 x64, Windows Server 2008 running Terminal Services, Windows Server 2022, Windows Server 2008, Windows 8 x64, Windows Server 2012, Windows Server 2003 x64, Windows Server 2003, Windows Server 2012 R2, Windows Server 2003 x64 running Terminal Services, Windows Server 2003 running Terminal Services, Windows 10, Windows 8.1, Windows Server 2008 R2 running Terminal Services, Windows 8, Windows 2000 Server running Terminal Services, Windows XP x64, Windows Me, Windows XP, Windows Vista x64, Windows 2000, Windows Server 2019, Windows NT (4.00/4.00 Server), Windows Vista, Windows 98 2nd Edition, Windows 7	
Linux Operating Systems Supported	OpenSUSE 15.1, Red Hat Linux 8.3, Debian 9.4, Red Hat Linux 7.9, SUSE Linux Enterprise Server 15 SP2, SUSE Linux Enterprise Server 12 SP5, Fedora 33, Fedora 32, Debian 10, Ubuntu 20.04, Ubuntu 18.04 LTS, OpenSUSE 15.2	
Apple Operating Systems Supported	Support is provided through AirPrint and AirScan only.	
Android Operating Systems Supported	Support is provided through Mopria® Print Service and Mopria Scan.	
Citrix MetaFrame	Microsoft Windows Server 2003 x64 running Terminal Services with Citrix Presentation Server 4.0 x64, 4.5 x64, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0, Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5, Microsoft Windows Server 2008 R2 Standard Edition running Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2003 and 2003 X64 Edition with Citrix XenApp 5.0, Microsoft Windows Server 2008 R2 Enterprise Edition running Citrix XenApp 6.0, 6.5, Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame Presentation Server 4.0, Microsoft Windows Server 2012 R2 Datacenter Edition running Citrix XenApp 7.5, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16, Microsoft Windows Server 2012 Datacenter Edition running Citrix XenApp 7.5, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16, Microsoft Windows Server 2012 Essentials running Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2018 R2 Datacenter Edition running Citrix XenApp 7.5, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16, Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix XenApp 5.0, Microsoft Windows Server 2012 Standard running Citrix XenApp 6.0, 6.5	
Novell Operating Systems Supported	Novell Open Enterprise Server 2 (SP3) on SuSE Linux Enterprise Server 10 SP4 (x86 and x64) 3, Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64), Novell NetWare 6.5 Open Enterprise Server, Novell Open Enterprise Server 15 (SP1) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64), Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 12 SP1 (x86 and x64)	
Other Operating Systems Supported	Virtually any platform supporting TCP/IP.	